



SAE STANDARD CONNECTIONS

M13010

SAE MALE O-RING BOSS TYPE - SAE J516/J514
SAE MACHO CON O-RING TIPO BOSS - SAE J516/J514



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M13010-04-04	6	1/4"	- 04	7/16" - 20	4,0	24,0	9,1		14	
M13010-04-06	6	1/4"	- 04	9/16" - 18	7,1	24,5	9,9		17	
M13010-06-06	10	3/8"	- 06	9/16" - 18	7,0	25,6	9,9		17	
M13010-06-08	10	3/8"	- 06	3/4" - 16	9,3	28,6	11,1		22	
M13010-08-08	12	1/2"	- 08	3/4" - 16	9,3	28,9	11,1		22	
M13010-08-10	12	1/2"	- 08	7/8" - 14	12,5	31,9	12,7		25	
M13010-10-12	16	5/8"	- 10	1.1/16" - 12	15,0	37,7	15,1		32	
M13010-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	39,5	15,1		32	
M13010-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	40,0	15,1		38	
M13010-16-16	25	1"	- 16	1.5/16" - 12	19,8	41,0	15,1		38	




M14310*

SAE SWIVEL MALE O-RING BOSS TYPE - SAE J516/J514
SAE MACHO GIRATORIO CON O-RING TIPO BOSS - SAE J516/J514

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M14310-04-04	6	1/4"	- 04	7/16" - 20	4,0	41,0	9,1			17
NEW M14310-04-06	6	1/4"	- 04	9/16" - 18	7,0	44,0	9,9			22
M14310-06-06	10	3/8"	- 06	9/16" - 18	7,0	45,9	9,9			22
M14310-06-08	10	3/8"	- 06	3/4" - 16	7,0	47,8	11,1			22
M14310-08-08	12	1/2"	- 08	3/4" - 16	9,3	50,9	11,1			27
M14310-08-10	12	1/2"	- 08	7/8" - 14	9,3	42,2	13,0			27
M14310-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	49,4	15,0			32
M14310-10-10	16	5/8"	- 10	7/8" - 14	9,3	41,4	13,0			27
M14310-12-12	19	3/4"	- 12	1.1/16" - 12	12,5	47,8	15,0			32

(*) Not to be used as a live swivel



M14390*

90° SAE SWIVEL MALE O-RING BOSS TYPE - SAE J516/J514
SAE MACHO GIRATORIO CON O-RING CODO COMPACTO DE 90°
TIPO BOSS - SAE J516/J514


PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E	H ₁	H ₂
M14390-06-06	10	3/8"	- 06	9/16" - 18	5,7	20,1	9,9	40,0	22	17
M14390-06-08	10	3/8"	- 06	3/4" - 16	7,0	20,1	11,1	44,4	22	22
M14390-08-08	12	1/2"	- 08	3/4" - 16	9,3	22,1	11,1	49,0	27	22
M14390-08-10	12	1/2"	- 08	7/8" - 14	9,3	27,5	13,0	47,5	27	27
M14390-10-10	16	5/8"	- 10	7/8" - 14	9,3	28,0	13,0	47,5	27	27
M14390-12-12	19	3/4"	- 12	1.1/16" - 12	12,5	27,5	15,0	55,5	32	32

(*) Brazed solution - Not to be used as a live swivel

SAE STANDARD CONNECTIONS

M22612


SAE FEMALE 45° CONE SEAT - SAE J516/J512 (THRUST-WIRE NUT)
SAE HEMBRA ASIENTO A 45° - SAE J516/J512 (TUERCA CON SEGURO)



PART. REF.		HOSE BORE		THREAD	DIMENSIONS mm					
		DN	inch	Size	T	B	A	C		H ₂
NEW	M22612-04-04	6	1/4"	- 04	7/16" - 20	4,0	15,5	8,2		17
	M22612-06-06	10	3/8"	- 06	5/8" - 18	7,0	16,6	10,8		22
	M22612-12-12	19	3/4"	- 12	1.1/16" - 14	15,0	22,7	14,4		32

M22692

90° SAE FEMALE SWEEP ELBOW 45° CONE SEAT - SAE J516/J512
(THRUST-WIRE NUT)
SAE HEMBRA CODO DE 90° ASIENTO A 45° - SAE J516/J512
(TUERCA CON SEGURO)



PART. REF.		HOSE BORE		THREAD	DIMENSIONS mm					
		DN	inch	Size	T	B	A	C	E	H ₂
	M22692-04-04	6	1/4"	- 04	7/16" - 20	4,0	28,3	8,0	27,0	17
	M22692-06-06	10	3/8"	- 06	5/8" - 18	7,0	35,5	10,8	33,0	22
	M22692-12-12	19	3/4"	- 12	1.1/6" - 14	15,0	62,0	14,4	58,0	32