


M12810

NPTF MALE 30° CONE SEAT - SAE J516
NPTF MACHO ASIENTO A 30° - SAE J516




PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M12810-03-02	5	3/16"	- 03	1/8" - 27	4,0	23,6	10,0		12	
M12810-03-04	5	3/16"	- 03	1/4" - 18	5,5	29,1	14,5		14	
M12810-04-02	6	1/4"	- 04	1/8" - 27	4,0	24,1	10,0		12	
M12810-04-04	6	1/4"	- 04	1/4" - 18	5,5	29,0	14,5		14	
M12810-04-06	6	1/4"	- 04	3/8" - 18	9,3	31,5	14,5		19	
M12810-04-08	6	1/4"	- 04	1/2" - 14	9,3	33,5	19,2		24	
M12810-05-04	8	5/16"	- 05	1/4" - 18	5,5	30,0	14,5		14	
M12810-05-06	8	5/16"	- 05	3/8" - 18	9,3	32,0	14,5		19	
M12810-06-04	10	3/8"	- 06	1/4" - 18	5,5	30,1	14,5		14	
M12810-06-06	10	3/8"	- 06	3/8" - 18	9,3	28,6	14,5		19	
M12810-06-08	10	3/8"	- 06	1/2" - 14	12,5	34,6	19,2		24	
M12810-08-06	12	1/2"	- 08	3/8" - 18	9,3	28,9	14,5		19	
M12810-08-08	12	1/2"	- 08	1/2" - 14	12,5	34,9	19,2		24	
M12810-08-12	12	1/2"	- 08	3/4" - 14	16,0	35,4	19,2		27	
M12810-10-08	16	5/8"	- 10	1/2" - 14	12,5	38,7	19,2		24	
M12810-10-12	16	5/8"	- 10	3/4" - 14	16,0	40,2	19,2		27	
M12810-12-12	19	3/4"	- 12	3/4" - 14	16,0	36,5	19,2		27	
M12810-12-08	19	3/4"	- 12	1/2" - 14	12,5	36,5	13,6		27	
M12810-12-16	19	3/4"	- 12	1" - 11,5	19,8	46,0	24,2		36	
M12810-16-12	25	1"	- 16	3/4" - 14	15,5	38,8	19,2		32	
M12810-16-16	25	1"	- 16	1" - 11,5	19,8	43,8	24,2		36	
M12810-16-20	25	1"	- 16	1.1/4" - 11,5	26,0	56,3	25,0		46	
M12810-20-20	31	1.1/4"	- 20	1.1/4" - 11,5	26,0	56,5	25,0		46	
M12810-24-24	38	1.1/2"	- 24	1.1/2" - 11,5	32,0	57,6	26,0		50	
M12810-32-32	51	2"	- 32	2" - 11,5	45,0	64,3	26,5		65	

SAE STANDARD CONNECTIONS

M14110*

NPTF SWIVEL MALE 30° CONE SEAT - SAE J516

NPTF MACHO GIRATORIO ROSCA ASIENTO A 30° - SAE J516




PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M14110-04-02	6	1/4"	- 04	1/8" - 27	3,0	41,9	10,0			17
M14110-04-04	6	1/4"	- 04	1/4" - 18	4,0	46,4	14,5			17
M14110-04-06	6	1/4"	- 04	3/8" - 18	7,0	46,4	14,5			19
M14110-06-04	10	3/8"	- 06	1/4" - 18	4,0	50,5	14,5			22
M14110-06-06	10	3/8"	- 06	3/8" - 18	7,0	50,5	14,5			22
M14110-06-08	10	3/8"	- 06	1/2" - 14	9,3	55,2	19,2			24
M14110-08-08	12	1/2"	- 08	1/2" - 14	9,3	59,0	19,2			27
M14110-12-12	19	3/4"	- 12	3/4" - 14	16,0	57,9	19,2			32
M14110-16-16	25	1"	- 16	1" - 11,5	19,8	65,8	24,2			38

(*) Not to be used as a live swivel

M22812

NPSM FEMALE 30° CONE (THRUST-WIRE NUT)

NPSM HEMBRA ASIENTO A 30° (TUERCA CON SEGURO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M22812-04-04	6	1/4"	- 04	1/4" - 18	4,0	17,5	4,2			19
M22812-06-06	10	3/8"	- 06	3/8" - 18	7,0	20,9	6,0			22
M22812-08-08	12	1/2"	- 08	1/2" - 14	9,3	22,8	6,5			27
M22812-12-12	19	3/4"	- 12	3/4" - 14	15,0	24,5	9,0			32
M22812-16-16	25	1"	- 16	1" - 11,5	19,8	27,3	10,5			38