


M37810

NPTF MALE 30° CONE SEAT - SAE J516
NPTF MACHO ASIENTO A 30° - SAE J516

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M37810-12-12	19	3/4"	- 12	3/4" - 14	16,0	43,3	19,2		32	
M37810-16-16	25	1"	- 16	1" - 11,5	19,0	49,5	24,2		41	
M37810-20-20	31	1.1/4"	- 20	1.1/4" - 11,5	26,0	61,0	25,0		46	
M37810-24-24	38	1.1/2"	- 24	1.1/2" - 11,5	32,0	62,5	26,0		50	
M37810-32-32	51	2"	- 32	2" - 11,5	42,0	66,5	26,5		70	



M47512

JIC FEMALE 37° CONE SEAT - SAE J516/J514 (THRUST-WIRE NUT)
JIC HEMBRA ASIENTO A 37° - SAE J516/J514 (TUERCA CON SEGURO)


PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M47512-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	31,3	14,2		32	32
M47512-16-16	25	1"	- 16	1.5/16" - 12	21,7	34,0	15,2		41	41
M47512-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	46,0	16,2		50	50
M47512-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	52,0	18,8		55	60
M47512-32-32	51	2"	- 32	2.1/2" - 12	42,0	49,5	24,0		70	75

SAE STANDARD CONNECTIONS

M47592

**90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516/J514
(THRUST-WIRE NUT)**

JIC HEMBRA CODO DE 90° ASIENTO A 37° - SAE J516/J514
(TUERCA CON SEGURO)




PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M47592-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	73,0	14,2	66,0		32
M47592-16-16	25	1"	- 16	1.5/16" - 12	21,7	82,5	15,2	77,5		41
M47592-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	98,5	16,2	92,0		50
M47592-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	115,5	18,8	106,0		60
M47592-32-32	51	2"	- 32	2.1/2" - 12	42,0	144,5	24,0	137,0		75

M47542

**45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516/J514
(THRUST-WIRE NUT)**

JIC HEMBRA CODO DE 45° ASIENTO A 37° - SAE J516/J514
(TUERCA CON SEGURO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M47542-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	86,5	14,2	33,0		32
M47542-16-16	25	1"	- 16	1.5/16" - 12	21,7	95,0	15,2	37,0		41
M47542-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	115,5	16,2	45,0		50
M47542-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	126,5	18,8	50,0		60